


AC EV CHARGING EXTENSION CORD

TYPE1 XCA-01

3.5KW	9KW
7KW	11KW


SPECIFICATIONS

TYPE1	Rated voltage	Rated current	Rated power	Model NO.
	AC110-240V	16A	3.5KW	SP-EV-XCA-01-AC16
		32A	7KW	SP-EV-XCA-01-AC32
		40A	9KW	SP-EV-XCA-01-AC40
		48A	11KW	SP-EV-XCA-01-AC48

FEATURE

Cable specification:	16A - 3.5KW - 3x12AWG+2x18AWG 32A - 7KW - 3x10AWG+2x18AWG 40A - 9KW - 2x9AWG+1x10AWG+2x18AWG 48A - 11KW - 2x8AWG+1x10AWG+2x18AWG
Mechanical life:	No-load plug in / pull out > 10,000 times
Plug dimensions:	L220 x W65 x H64 (mm)
Socket dimensions:	W70 x H70 (mm)
Protection rank:	IP55
Work temperature:	-30°C~+50°C
Materials:	EV charging cable TPE
Case material:	Thermoplastic(flame retardant grade UL94-0)

CUSTOMIZATION

Cable length:	5m / 7m / 10m
Plug color:	
Logo printing:	Laser



Multiple protection

High temperature, over voltage, under voltage, ground, over current, leakage protection.



Dust Proof

Dust cover on socket side.

